

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 043 725 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
11.10.2000 Bulletin 2000/41(51) Int. Cl.<sup>7</sup>: G11B 27/30, G11B 20/12,  
H04N 5/7826

(21) Application number: 00302885.9

(22) Date of filing: 05.04.2000

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 06.04.1999 JP 9853499

(71) Applicant: SONY CORPORATION  
Tokyo 141 (JP)

(72) Inventors:

- Senshu, Yoichiro,  
c/o Intellectual Property Dept.  
Shinagawa-ku, Tokyo 141 (JP)
- Higashio, Yashuhiro,  
c/o Intellectual Property Dep  
Shinagawa-ku, Tokyo 141 (JP)


(74) Representative:

Pilch, Adam John Michael et al  
D. YOUNG & CO.,  
21 New Fetter Lane  
London EC4A 1DA (GB)

## (54) Magnetic recording and/or reproduction methods and apparatus

(57) In a recording and/or reproduction method for recording compressed digital data on magnetic tape by a helical scanning method or for reproducing compressed digital data recorded on magnetic tape by the helical scanning method, a first recording area (3), including an audio sector (AR AUDIO), and a second recording area (4), including a track-synchronization-information sector (ITI), a video sector or a video-and-audio-mixed sector (AUDIO-VIDEO (EMBEDDED)) in which audio data and video data are mixed, a sub-code sector (SUB-CODE), and a search-data sector (SEARCH) in which data used in variable-speed reproduction is recorded, are sequentially disposed in the direction from the top to the end of each track on the magnetic tape with an interference area (5) disposed therebetween. Data is continuously recorded in each sector in the first recording area (3) and the second recording area (4). In the second recording area (4), the sub-code sector (SUB-CODE) or the search-data sector (SEARCH) is disposed after the video sector or the video-and-audio-mixed sector (AUDIO-VIDEO (EMBEDDED)).

FIG. 3



EP 1 043 725 A2

## Description

[0001] The present invention relates to magnetic recording and/or reproduction apparatus and methods therefor, and more particularly, to a magnetic recording and/or reproduction apparatus and a method therefor, in which digital data is recorded by a helical scanning method or reproduced.

[0002] Portable digital video tape recorders including cameras (digital camcorders) and installation-type digital video tape recorders have been available these days, which are recording and reproduction apparatuses for recording digital video signals and digital audio signals into magnetic tape.

[0003] As a recording method for the above digital video tape recorders, a so-called DV method (IEC 61834 Helical scan digital video tape cassette recording system using 6.35 mm magnetic tape for consumers - 525/60, 625/50, 1125/60, and 1250/50 systems) is used. Reference is directed to two related disclosures, US-A-5 926 604 and US-A-6 028 726.

[0004] In the DV method, video tape 6.35 mm (= 1/4 inches) wide is used, which is narrower than video tape used in related analog video tape recorders by their recording methods, such as an 8-mm method (IEC 60843 Helical scan video tape cassette recording system using 8 mm magnetic tape for consumers).

[0005] In the DV method, although the tape width is smaller than that conventionally used, since a signal to be recorded is compressed and a recording density is increased, the DV method allows higher-quality recording for a longer period than recording methods for related analog video tape recorders.

[0006] Fig. 4 shows a track structure in the DV method. From the top of a track, an insert-and-track-information (ITI) sector serving as a time-axis reference during so-called after recording, an interference area (ITG: inter-track gap) (GAP), an audio (Audio) sector, another interference area (GAP), a video (Video) sector, yet another interference area (GAP), and a sub-code (Sub-code) sector are sequentially disposed.

[0007] In the DV method, one frame of a video signal conforming to the NTSC system is recorded into each of a total of 10 (12 for PAL) tracks. This means that a track has a constant relationship with a frame.

[0008] Therefore, when a desired video (frame) is searched for by fast forwarding magnetic tape while video is viewed, namely, during a variable-speed reproduction using a so-called search function, for example, since a track has a constant relationship with a frame, even if reproduction starts at any position in magnetic tape, video can be displayed after data is read from a predetermined number of tracks, and it is very easy to identify the position of the desired frame in the magnetic tape.

[0009] In a method for recording digital data which includes a video signal and an audio signal compressed by the MPEG-2 method, for example, since a track does not have a constant relationship with a frame due to the characteristics of the compression process, it is difficult to identify the position of a desired frame in magnetic tape. In addition, when reproduction starts at any position in the magnetic tape, if all of one frame of a video signal is not recorded at the position, video cannot be displayed.

[0010] In the method for recording digital data which includes a video signal and an audio, signal compressed by the MPEG-2 method, it is known that data especially for variable-speed reproduction, such as for searching, namely, search data, is recorded in each track of magnetic tape together with other types of data.

[0011] Depending on a position where search data is recorded on a track, however, the following problem arises.

[0012] An RF output obtained from each track differs between a normal reproduction mode (FWD) and a variable-speed reproduction mode, such as a high-speed reproduction mode (Cue & review) and a fast-forward or rewinding reproduction mode (FF & rewind) as shown in Figs. 5 to 7. In FWD, a successful RF level is maintained at both starting position and ending position of a head in a track, whereas an RF output deteriorates at the start position of the head in a track where a rotating drum provides a thick air film in Cue & review (at about a speed five times to 30 times the normal reproduction speed). In FF & rewind (at about a speed 30 times to 200 times the normal reproduction speed), an RF output deteriorates near the ending position of a head in a track as well as the starting position in the track.

[0013] Therefore, in the DV method, for example, since position information (such as a track number) to be referenced during FF & rewind on the magnetic tape is recorded in the sub-code (Sub-code) sector, which is located near the ending position of a head in a track as shown in Fig. 4, it is difficult to obtain a necessary RF output.

[0014] When a non-standard signal (a signal output from a video-game unit or an analog-type recording and reproduction apparatus during a variable-speed reproduction, in which the time axis shifts from the standard of the NTSC system or the PAL system) is recorded by a digital-type recording and reproduction apparatus, if the rotation of a rotating drum tracks the non-standard signal, the length of each track into which digital data having a constant clock frequency is recorded may be extended or contracted.

[0015] As shown in Fig. 8, if the length of a track is extended, since the ending position of the head in the track shifts, data may be recorded into an area where an RF output characteristic is not assured on magnetic tape.

[0016] This issue is likely to affect especially methods in which a sub-code (Sub-code) sector is located near the ending position of a head in a track, such as the DV method. If data recorded into the sub-code (Sub-code) sector cannot be read, the destination is not identified in searching, causing a problem in the operations of the apparatus.

[0017] Accordingly, it is an aim of at least an embodiment of the present invention to improve RF and search characteristics when data dedicated to variable-speed reproduction, such as a search, namely, search data, is recorded into magnetic tape, in a magnetic recording and reproduction apparatus and a method therefor in which compressed digital data is recorded into the magnetic tape by a helical scanning method or compressed digital data recorded into the magnetic tape by the helical scanning method is reproduced.

[0018] One aspect of the present invention provides a recording and/or reproduction method for recording compressed digital data on magnetic tape by a helical scanning method or for reproducing compressed digital data recorded on magnetic tape by the helical scanning method, including the steps of disposing sequentially in the direction from the top to the end of each track on the magnetic tape a first recording area, including an audio sector, and a second recording area, including a track-synchronization-information sector, a video sector or a video-and-audio-mixed sector in which audio data and video data are mixed, a sub-code sector, and a search-data sector in which data used in variable-speed reproduction is recorded, with an interference area disposed therebetween; recording data continuously in each sector in the first recording area and the second recording area; and disposing the sub-code sector or the search-data sector after the video sector or the video-and-audio-mixed sector in the second recording area.

[0019] Since the sub-code sector or the search-data sector is disposed at a position where a successful RF output characteristic is obtained in each track, the RF characteristic and that in the variable-speed reproduction are maintained at a successful level.

[0020] Another aspect of the present invention provides recording and/or reproduction apparatus for recording compressed digital data on magnetic tape by a helical scanning method or for reproducing compressed digital data recorded on magnetic tape by the helical scanning method, including recording means for disposing sequentially in the direction from the top to the end of each track on the magnetic tape a first recording area, including an audio sector, and a second recording area, including a track-synchronization-information sector, a video sector or a video-and-audio-mixed sector in which audio data and video data are mixed, a sub-code sector, and a search-data sector in which data used in variable-speed reproduction is recorded, with an interference area disposed therebetween, and for recording data continuously in each sector in the first recording area and the second recording area, wherein the sub-code sector or the search-data sector is disposed after the video sector or the video-and-audio-mixed sector in the second recording area.

[0021] Since the sub-code sector or the search-data sector is disposed at a position where a successful RF output characteristic is obtained in each track, the RF characteristic and that in the variable-speed reproduction are maintained at a successful level.

[0022] The video sector or the video-and-audio-mixed sector, the sub-code sector, and the search-data sector may be disposed in that order in the second recording area in the direction from the top to the end of each track. In this case, data required for variable-speed reproduction is collectively disposed at the ending position (the last reading portion) of the head in a recording track, where a rotating drum provides a thin air film and a stable RF output is obtained. Therefore, the RF characteristic and that in the variable-speed reproduction are maintained at an extremely successful level.

[0023] The invention will now be described by way of example with reference to the accompanying drawings, throughout which like parts are referred to by like references, and in which:

Fig. 1 is a view of a track pattern on magnetic tape, which can be used with magnetic recording and/or reproduction apparatus and a method therefor according to an embodiment of the present invention;

Fig. 2 is a view showing a tape wrap angle on a rotating drum, according to the embodiment of Fig. 1;

Fig. 3 is a view of a data pattern in a track, according to the embodiment of Fig. 1;

Fig. 4 is a view of a data pattern in a track in a related recording method (DV method);

Fig. 5 is a view of an RF waveform during a normal reproduction mode (FWD), relating to the data track pattern of Fig. 4;

Fig. 6 is a view of an RF waveform during a high-speed reproduction mode (Cue & review), relating to the technique of Fig. 4;

Fig. 7 is a view of an RF waveform during a fast-forward or rewinding reproduction mode (FF & rewind) of the Fig. 4 technique; and

Fig. 8 a view of an RF waveform during recording of a non-standard signal, in the technique of Fig. 4.

[0024] A magnetic recording and/or reproduction apparatus and a method therefor according to an embodiment of the present invention will be described below by referring to the drawings.

[0025] The following embodiment describes a case in which the present invention is applied to a magnetic recording and reproduction method for recording and reproducing digital data compressed by the Moving Picture Experts Group (MPEG) 2 method or the like into and from magnetic tape 3.81 mm (= 3/20 inches) wide, and is also applied to a magnetic recording and reproduction apparatus using the magnetic recording and reproduction method.

[0026] In a magnetic recording and reproduction method according to the present invention, compressed digital

data is recorded into magnetic tape by a helical scanning method or compressed digital data recorded into magnetic tape by the helical scanning method is reproduced. In each track on the magnetic tape, there are sequentially disposed in the direction from the top to the end of each track a first recording area which includes an audio sector, and a second recording area which includes track-synchronization-information sector, a video sector or a video-and-audio-mixed sector in which audio data and video data are mixed, a sub-code sector, and a search-data sector in which data used during a variable-speed reproduction is recorded, with an interference area disposed therebetween. Data is continuously recorded in each sector in the first and second recording areas. In the second recording area, the sub-code sector or the search-data sector is disposed after the video sector or the video-and-audio-mixed sector.

[0027] In a magnetic recording and reproduction apparatus according to the present invention, compressed digital data is recorded into magnetic tape by a helical scanning method or compressed digital data recorded into magnetic tape by the helical scanning method is reproduced. The magnetic recording and reproduction apparatus is provided with recording means for sequentially disposing in each track on the magnetic tape in the direction from the top to the end of each track a first recording area which includes an audio sector, and a second recording area which includes a track-synchronization-information sector, a video sector or a video-and-audio-mixed sector in which audio data and video data are mixed, a sub-code sector, and a search-data sector in which data used during a variable-speed reproduction is recorded, with an interference area disposed therebetween; and for continuously recording data in each sector of the first and second recording areas. In the second recording area, the sub-code sector or the search-data sector is disposed after the video sector or the video-and-audio-mixed sector.

[0028] The following Table 1 indicates parameters used in a magnetic recording and reproduction method (hereinafter called the present format) according to the present invention, for recording and reproducing digital data compressed by the MPEG-2 method or the like into and from magnetic tape 3.81 mm (= 3/20 inches) wide, and also used in a magnetic recording and reproduction apparatus employing the present format.

Table 1

Parameters	Values
Diameter of rotating drum	21.7 mm
Speed of rotating drum	6,480 rpm
Track count per one rotation of rotating drum	1
Lead angle of rotating drum	5.067 degrees
Recording-track angle ( $\theta_r$ )	5.0704 degrees
Track pitch	4.0 $\mu\text{m}$
Tape speed	4.888 mm/sec
Relative speed	7.358 m/sec
Recording rate	51.516 Mbps
Recording density on actual surface	1.129 Gbpi <sup>2</sup>
Recording density on source surface	1.004 Gbpi <sup>2</sup>
Minimum recording wavelength	0.286 $\mu\text{m}$
Effective track length	31.793 mm
Sync lag	6.127 $\mu\text{s}$
Tr0 azimuth angle	-20 or 25
Tr1 azimuth angle	+20 or 25
Effective wrap angle	168 degrees
Tape width	3.81 mm
Effective-area starting height	0.5 mm
Track-center height	1.590 mm

[0029] Fig. 1 shows a track pattern used when a digital signal is recorded into magnetic tape 1 having a tape width

of 3.81 mm, which is used in the present format.

[0030] As shown in Table 1 and Fig. 1, in the present format, a video signal and an audio signal are recorded into tracks Tr0 and Tr1 alternately by two heads provided for a rotating drum 2 having a diameter of 21.7 mm which rotates 6,480 rpm against the magnetic tape 1, per one rotation of the rotating drum 2.

[0031] In other words, the rotating drum 2 is provided, for example, with two magnetic heads having different azimuth angles, disposed at positions 180 degrees apart. These two magnetic heads scan the magnetic tape 1 at a predetermined angle ( $\theta_r = 5.07036$  degrees) against the running direction of the magnetic tape 1 to form the track pattern shown in Fig. 1.

[0032] Fig. 2 shows a tape wrap angle on the rotating drum 2 in the present format.

[0033] In the present format, the magnetic tape 1 is wound on the rotating drum 2 at an angle of 168 degrees, as shown in Fig. 2. A signal is recorded into one track on the magnetic tape 1 when one magnetic head moves within a tape wrap angle of 168 degrees.

[0034] During data recording, a head used for recording data is changed every time the rotating drum 2 rotates by 360 degrees. More specifically, for example, one head records data into the track Tr0 at a first rotation of the rotating drum 2 and the other head having a different azimuth angle records data into the track Tr1 at the next rotation.

[0035] During data reproduction, the two heads always reproduce RF data per one rotation of the rotating drum 2. This is called a double-density reproduction (so-called non-tracking) method. According to this method, since data is reproduced from one track by the two heads with a slight shift, it is advantageous that a compatibility problem caused by a track curve is eased.

[0036] Fig. 3 shows a data pattern in the track Tr0 or Tr1 in the present format.

[0037] In the present format, an effective wrap angle is 168 degrees as shown in Fig. 1 and Fig. 3. Within this effective wrap angle, the first recording area (sub area) 3 having 11,016 bits, the second recording area (main area) 4 having 210,342 bits, and the interference area (GAP) 5 having 1,242 bits sandwiched thereby are disposed.

[0038] At the pre-stage and the post-stage of the effective wrap angle, an erase-margin-in (Em-in) sector having 1,260 bits and an erase-margin-out (Em-out) sector having 3,078 bits are disposed as erase margins.

[0039] The first recording area 3 includes sectors from the starting position of a head (in the direction from the top to the end) in a track in the order of a track-pre-amble (Tr-pre) sector having 2,053 bits, an audio (Audio) sector having 8,208 bits for after recording, and an audio-post-amble (Audio-post) sector having 756 bits, as shown in Fig. 3.

[0040] The second recording area 4 includes sectors from the starting position of a head in a track in the order of an ITI-pre-amble (ITI-pre) sector having 297 bits, a track-synchronization-information (ITI) sector having 1,620 bits, a video-and-audio-mixed (Audio-Video (Embedded)) sector having 186,714 bits, in which video data and audio data are mixed, a sub-code (Sub-code) sector having 1,620 bits, a search-data (Search) sector having 17,442 bits, in which data used during a variable-speed reproduction is recorded, and a track-post-amble (Tr-post) sector having 2,649 bits.

[0041] A feature of the track pattern on the magnetic tape 1 in the present format is that, as an interference area in which actual data is not recorded, only the interference area 5 is provided between the first recording area 3 and the second recording area 4, and an interference area is not provided for portions such as that between the video-and-audio-mixed (Audio-Video) sector and the sub-code (Sub-code) sector.

[0042] Therefore, the rate of the interference area 5 to the effective data zone in one track, the effective data zone being formed of the track-pre-amble (Tr-pre) sector, the audio (Audio) sector, the audio-post-amble (Audio-post) sector, the interference area 5, the ITI-pre-amble (ITI-pre) sector, the track-synchronization-information (ITI) sector, the video-and-audio-mixed (Audio-Video) sector, the sub-code (Sub-code) sector, and the track-post-amble (Tr-post) sector, is about 0.6% ( $1062/230550 = 0.005$ ), which is extremely smaller than the corresponding value in the DV method, about 2%. This means that the data area on the magnetic tape is more efficiently used in the present format.

[0043] To reduce the rate of the interference area, which is not an effective data area in one track, as much as possible, the following configuration is used in the present format.

[0044] For after recording into the audio (Audio) sector, the track-synchronization-information (ITI) sector, which serves as a time-axis reference for after recording, is placed at the subsequent side of the audio (Audio) sector and the timing obtained by the previous head scanning is stored and accumulated to adjust the timing for after recording into the audio (Audio) sector. Therefore, it is unnecessary to place an interference area between the track-synchronization-information (ITI) sector and the video-and-audio-mixed (Audio-Video) sector.

[0045] In the present format, after recording is not performed in the sub-code (Sub-code) sector. A time code and additional data obtained during the original data recording are recorded into the sub-code sector and a location during search is read therefrom. A marker used for later rewriting is stored, for example, in a memory provided for the cassette of the magnetic tape 1. Therefore, an interference area conventionally disposed between the video-and-audio-mixed (Audio-Video) sector and the sub-code sector can be removed.

[0046] Another feature of the track pattern on the magnetic tape 1 in the present format is that data is continuously recorded into the sub-code (Sub-code) sector and the search-data (Search) sector after the video-and-audio-mixed (Audio-Video) sector in the second recording area 4.

[0047] As described before, video cannot be displayed during a variable-speed reproduction by the use of data compressed by the MPEG-2 method or the like, recorded into the video-and-audio-mixed (Audio-Video) sector, data (mainly video data) used during variable-speed reproduction is recorded in the search-data (Search) sector.

[0048] Since the sub-code sector needs to be read during variable-speed reproduction of the magnetic tape 1, it is disposed near the ending position of the head in a track, where an RF output is stable and the rotating drum 2 produces a thin air film even in a variable-speed reproduction, in which the magnetic tape 1 runs fast.

[0049] The audio (Audio) sector for after recording is disposed near the starting position of the head in a track, where an RF output tends to be unstable during variable-speed reproduction. This is because it is not necessary to output audio during variable-speed reproduction.

[0050] The erase margin sectors Em-in and Em-out are provided at the pre-stage and the post-stage of the effective wrap angle, namely, at the starting position and the ending position of the head in a track to prevent, when data is written into a track where another data has been recorded, previous data from remaining due to the positional shift of the track.

[0051] Various reproduction modes for the magnetic tape 1 where data is recorded by the present format, and sectors required for each of the various reproduction modes will be described below.

[0052] In the normal reproduction (FWD) mode, all sectors except the search-data (Search) sector are needed. In the high-speed reproduction (Cue & review) mode, the search-data (Search) sector, used for displaying video reproduced at a variable speed, and the sub-code (Sub-code) sector, used for obtaining a track number and a time code, are required. In the fast-forward or rewinding reproduction (FF & rewind) mode, only the sub-code (Sub-code) sector, used for obtaining a track number and a time code, is required.

[0053] In this way, sectors required for reproducing data are limited in variable-speed reproduction, namely, the high-speed reproduction mode and the fast-forward or rewinding reproduction mode.

[0054] Since the present format has the data pattern described above for tracks Tr0 and Tr1, both sub-code (Sub-code) sector and search-data (Search) sector are reproduced easily in the high-speed reproduction mode. In addition, in the fast-forward or rewinding reproduction mode, where a higher speed is used than in the high-speed reproduction mode, even if an RF signal near the ending position of the head in a track deteriorates, the deterioration of an RF output is unlikely to affect because the sub-code (Sub-code) sector, required to be reproduced, is disposed more inside.

[0055] In the normal reproduction, even if an RF signal near the ending position of the head in a track deteriorates, since search data recorded in the search-data (Search) sector disposed there is not used, video, audio, and a time code work well.

[0056] Unlike the DV method, since sub-code data is not recorded near the ending position of the head in a track, the deterioration of an RF output near the ending position does not affect in the present format. Therefore, during the fast-forward or rewinding reproduction mode, when a predetermined recording location is searched for according to sub-code data while the magnetic tape 1 is fed at a high speed, an inconvenience does not occur in which the predetermined location cannot be searched for because sub-code data cannot be read. The fast-forward or rewinding reproduction mode can be implemented at a higher speed.

[0057] Even if a track is extended because a non-standard signal is recorded and the ends (the starting and ending positions of the head) of the track exceeds a recording and reproduction area on magnetic tape, data recorded into the video-and-audio-mixed (Audio-Video) sector, which is required for various types of control in a recording and reproduction apparatus can be read in the present format, and various types of control are not affected. In the same way, since the video-and-audio-mixed (Audio-Video) sector, including video data, is disposed more inside than the video-and-audio-mixed (Audio-Video) sector in a track, it is not affected. Data recorded in the search-data (Search) sector, which is used in the high-speed reproduction mode, is affected to some extent and disturbed, but the essential function still works.

[0058] As described above in detail, according to the format used in a magnetic recording and reproduction apparatus and a method therefor of the present invention, since video data compressed by the MPEG-2 method and the like cannot be reproduced during a variable-speed reproduction, the search-data section used during the variable-speed reproduction is separately provided near the ending position of the head in a recording track and the sub-code sector is also provided therefore to enhance RF characteristics and those during the variable-speed reproduction. If this object is achieved, the order in which the sectors forming the track data pattern are arranged in a track can be modified appropriately.

[0059] Interference areas, which are ineffective data areas in a track, are reduced. The rate of interference areas to all data recording areas is about 0.6%, which is lower by 1.4% than about 2% in the DV method. Data can be recorded more.

[0060] Therefore, with the amount of data to be recorded being the same, magnetic tape used is reduced. With the same amount of magnetic tape being used, the amount of data to be recorded is increased, which can improve sound quality and image quality.

[0061] In addition, with the same amount of magnetic tape being used, since the frequency of a data recording sig-

nal can be lowered to make the minimum recording wavelength to be recorded on magnetic tape longer, a load applied to an electromagnetic transduction system, such as magnetic tape and magnetic heads, is reduced.

[0062] The arrangement order of the interference area 5 and the sectors excluding the sub-code (Sub-code) sector and the search-data (Search) sector, forming the data pattern in a track in the present format, is not limited to that described above.

[0063] The specific shape and construction of each section shown in the above embodiment merely indicate a specific example embodiment of the present invention. The technical scope of the present invention is not limited thereby.

## Claims

1. A recording and/or reproduction method for recording compressed digital data on magnetic tape by a helical scanning method or for reproducing compressed digital data recorded on magnetic tape by the helical scanning method, comprising the steps of:

disposing sequentially in the direction from the top to the end of each track on the magnetic tape a first recording area, including an audio sector, and a second recording area, including a track-synchronization-information sector, a video sector or a video-and-audio-mixed sector in which audio data and video data are mixed, a sub-code sector, and a search-data sector in which data used in variable-speed reproduction is recorded, with an interference area disposed therebetween;

recording data continuously in each sector in the first recording area and the second recording area; and disposing the sub-code sector or the search-data sector after the video sector or the video-and-audio-mixed sector in the second recording area.

2. A recording and/or reproduction method according to Claim 1, wherein the video sector or the video-and-audio-mixed sector, the sub-code sector, and the search-data sector are disposed in that order in the second recording area in the direction from the top to the end of each track.

3. A recording and/or reproduction apparatus for recording compressed digital data on magnetic tape by a helical scanning method or for reproducing compressed digital data recorded on magnetic tape by the helical scanning method, comprising:

recording means for disposing sequentially in the direction from the top to the end of each track on the magnetic tape a first recording area, including an audio sector, and a second recording area, including a track-synchronization-information sector, a video sector or a video-and-audio-mixed sector in which audio data and video data are mixed, a sub-code sector, and a search-data sector in which data used in variable-speed reproduction is recorded, with an interference area disposed therebetween, and for recording data continuously in each sector in the first recording area and the second recording area;

wherein the sub-code sector or the search-data sector is disposed after the video sector or the video-and-audio-mixed sector in the second recording area.

4. A recording and/or reproduction apparatus according to Claim 3, wherein the video sector or the video-and-audio-mixed sector, the sub-code sector, and the search-data sector are disposed in that order in the second recording area in the direction from the top to the end of each track.

FIG. 1






FIG. 2





FIG. 3



AUDIO ..... AUDIO SECTOR  
 ITI ..... TRACK-SYNCHRONIZATION-INFORMATION SECTOR  
 AUDIO-VIDEO .... VIDEO-AND-AUDIO-MIXED SECTOR  
 SUB-CODE ..... SUB-CODE SECTOR  
 SEARCH ..... SEARCH-DATA SECTOR

FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8





(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
**18.02.2004 Bulletin 2004/08**

(51) Int Cl.7: **G11B 20/12, G11B 27/30**

(43) Date of publication A2:  
**11.10.2000 Bulletin 2000/41**

(21) Application number: **00302885.9**

(22) Date of filing: **05.04.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
 Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
 • **Senshu, Yoichiro, c/o Intellectual Property Dept. Shinagawa-ku, Tokyo 141 (JP)**  
 • **Higashio, Yashuhiro, c/o Intellectual Property Dep Shinagawa-ku, Tokyo 141 (JP)**

(30) Priority: **06.04.1999 JP 9853499**

(71) Applicant: **SONY CORPORATION**  
**Tokyo 141 (JP)**


(74) Representative: **Pilch, Adam John Michael et al D. YOUNG & CO., 21 New Fetter Lane London EC4A 1DA (GB)**

(54) **Magnetic recording and/or reproduction methods and apparatus**

(57) In a recording and/or reproduction method for recording compressed digital data on magnetic tape by a helical scanning method or for reproducing compressed digital data recorded on magnetic tape by the helical scanning method, a first recording area (3), including an audio sector (AR AUDIO), and a second recording area (4), including a track-synchronization-information sector (ITI), a video sector or a video-and-audio-mixed sector (AUDIO-VIDEO (EMBEDDED)) in which audio data and video data are mixed, a sub-code sector (SUB-CODE), and a search-data sector

(SEARCH) in which data used in variable-speed reproduction is recorded, are sequentially disposed in the direction from the top to the end of each track on the magnetic tape with an interference area (5) disposed therebetween. Data is continuously recorded in each sector in the first recording area (3) and the second recording area (4). In the second recording area (4), the sub-code sector (SUB-CODE) or the search-data sector (SEARCH) is disposed after the video sector or the video-and-audio-mixed sector (AUDIO-VIDEO (EMBEDDED)).

FIG. 3





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 00 30 2885

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	EP 0 712 127 A (SONY CORP) 15 May 1996 (1996-05-15) * column 8, line 32 - column 9, line 6; figures 6-8 *	1-4	G11B20/12 G11B27/30
A	--- PATENT ABSTRACTS OF JAPAN vol. 1996, no. 02, 29 February 1996 (1996-02-29) & JP 07 284051 A (MATSUSHITA ELECTRIC IND CO LTD), 27 October 1995 (1995-10-27) * abstract *	1-4	
A	--- US 5 377 051 A (FUHRER JACK S ET AL) 27 December 1994 (1994-12-27) * column 19, line 21 - line 57; figure 7 *	1-4	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G11B H04N
The present search report has been drawn up for all claims			
Place of search <b>MUNICH</b>		Date of completion of the search <b>17 December 2003</b>	Examiner <b>Schinnerl, A</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 02 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 2885

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-12-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0712127	A	15-05-1996	JP	8195072 A	30-07-1996
			AT	195623 T	15-09-2000
			AU	707351 B2	08-07-1999
			AU	3781695 A	23-05-1996
			AU	707367 B2	08-07-1999
			AU	3790295 A	23-05-1996
			BR	9505186 A	28-10-1997
			CA	2162549 A1	15-05-1996
			CA	2162788 A1	15-05-1996
			CA	2162789 A1	15-05-1996
			CN	1132445 A	02-10-1996
			CN	1133531 A	16-10-1996
			CN	1131369 A	18-09-1996
			DE	69518389 D1	21-09-2000
			DE	69518389 T2	29-03-2001
			EP	0712127 A2	15-05-1996
			EP	0712123 A2	15-05-1996
			EP	0712247 A2	15-05-1996
			ES	2149324 T3	01-11-2000
			JP	3446372 B2	16-09-2003
			JP	8223535 A	30-08-1996
			JP	8195723 A	30-07-1996
			US	5835668 A	10-11-1998
			US	5859949 A	12-01-1999
			US	5845043 A	01-12-1998
			US	5850501 A	15-12-1998
			US	5845042 A	01-12-1998
			US	6115531 A	05-09-2000
			US	6028726 A	22-02-2000
JP 07284051	A	27-10-1995	CN	1115456 A ,B	24-01-1996
			DE	69521225 D1	19-07-2001
			DE	69521225 T2	16-05-2002
			DE	69522348 D1	27-09-2001
			DE	69522348 T2	13-06-2002
			DE	69527157 D1	25-07-2002
			DE	69527157 T2	07-11-2002
			DE	69530875 D1	26-06-2003
			EP	0673158 A2	20-09-1995
			EP	0933935 A1	04-08-1999
			EP	0935391 A1	11-08-1999
			EP	0928106 A2	07-07-1999
			EP	0933936 A2	04-08-1999
			KR	188246 B1	01-06-1999
			US	6141487 A	31-10-2000

EPO FORM P0489

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82



ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 00 30 2885

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-12-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5377051 A	27-12-1994	US 5778143 A	07-07-1998
		US 5576902 A	19-11-1996
		US 5673358 A	30-09-1997
-----			

EPO FORM P0439

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82